

Liebert EXL S1 UPS, 100-1200 kW

Model Specifications Overview

Models	Power Rating	Input Voltage	Output Voltage	Efficiency	Wiring	Height	Width	Depth	Weight
Liebert EXL S1 100 kVA	100 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	500 mm	900 mm	370 kg
Liebert EXL S1 120 kVA	120 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	500 mm	900 mm	370 kg
Liebert EXL S1 160 kVA	160 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	750 mm	900 mm	510 kg
Liebert EXL S1 300 kVA	300 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	1000 mm	900 mm	725 kg
Liebert EXL S1 400 kVA	400 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	1000 mm	900 mm	725 kg
Liebert EXL S1 500 kVA	500 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	1250 mm	900 mm	990 kg
Liebert EXL S1 600 kVA	600 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	1600 mm	900 mm	1135 kg
Liebert EXL S1 800 kVA	800 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	2000 mm	900 mm	1550 kg
Liebert EXL S1 1000 kVA	1000 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	2650 mm	900 mm	2275 kg
Liebert EXL S1 1200 kVA	1200 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	2650 mm	900 mm	2275 kg
Liebert EXL S1 200 kVA	200 kVA	400 VAC	400 VAC	up to 99% (Dynamic Online)	3Ph or 3Ph + N	1950 mm	750 mm	900 mm	510 kg