

Liebert EXS UPS, 10-40 kVA

Model Specifications Overview

Models	Power Rating	Input Voltage	Output Voltage	Efficiency	Wiring	Height	Width	Depth	Weight
Liebert EXS 10 kVA	10 kVA	380 / 400 / 415 VAC	380/400/415 VAC (3-ph.) or 220/230/240 VAC (1-ph)	Up to 96.2%	three-phase + neutral	1300 mm	335 mm	650 mm	85 kg (no batt)
Liebert EXS 15 kVA	15 kVA	380 / 400 / 415 VAC	380/400/415 VAC (3-ph.) or 220/230/240 VAC (1-ph)	Up to 96.2%	three-phase + neutral	1300 mm	335 mm	650 mm	85 kg (no batt)
Liebert EXS 20 kVA	20 kVA	380 / 400 / 415 VAC	380/400/415 VAC (3-ph.) or 220/230/240 VAC (1-ph)	Up to 96.2%	three-phase + neutral	1300 mm	335 mm	650 mm	85 kg (no batt)
Liebert EXS 30 kVA	30 kVA	380 / 400 / 415 VAC	380/400/415 VAC (3-ph.)	Up to 96.2%	three-phase + neutral	1600 mm	440 mm	750 mm	200 (no batt)
Liebert EXS 40 kVA	40 kVA	380 / 400 / 415 VAC	380/400/415 VAC (3-ph.)	Up to 96.2%	three-phase + neutral	1600 mm	440 mm	750 mm	200 (no batt)