

# Liebert NXC UPS, 10-200 kVA

## Model Specifications Overview

Models	Power Rating	Input Voltage	Output Voltage	Efficiency	Height	Width	Depth	Weight
Liebert NXC 10 kVA	10 kVA / 9 kW	380 / 400 / 415 VAC	380 / 400 / 415 (1ph) - 220 / 230 / 240 VAC (3ph)	94.4% (100% load)	1240 mm	500 mm	860 mm	115 / 215 kg
Liebert NXC 15 kVA	15 kVA / 13.5 kW	380 / 400 / 415 VAC	380 / 400 / 415 (1ph) - 220 / 230 / 240 VAC (3ph)	94.5% (100% Load)	1240 mm	500 mm	860 mm	115 / 215 kg
Liebert NXC 20 kVA	20 kVA / 18 kW	380 / 400 / 415 VAC	380 / 400 / 415 (1ph) - 220 / 230 / 240 VAC (3ph)	94.2% (100% Load)	1240	500	860	115 / 215
Liebert NXC 30 kVA	30 kVA / 27 kW	380 / 400 / 415 VAC	380 / 400 / 415 (1ph) - 220 / 230 / 240 VAC (3ph)	94.7% (100% Load)	1600 mm	600 mm	850 mm	210 / 600 kg
Liebert NXC 40 kVA	40 kVA / 36 kW	380 / 400 / 415 VAC	380 / 400 / 415 VAC (3ph)	94.4% (100% Load)	1600 mm	600 mm	850 mm	210 / 600 kg
Liebert NXC 60 kVA	60 kVA / 54 kW	380 / 400 / 415 VAC	380 / 400 / 415 VAC (3ph)	95.3% (100% Load)	1600 mm	600 mm	850 mm	225 / 615 kg
Liebert NXC 80 kVA	80 kVA / 80 kW	380 / 400 / 415 VAC	380 / 400 / 415 VAC (3ph)	95.7% (100% Load)	1600 mm	600 mm	1000 mm	285 / 313 kg
Liebert NXC 100 kVA	100 kVA / 100 kW	380 / 400 / 415 VAC	380 / 400 / 415 VAC (3ph)	95.7% (100% Load)	1600 mm	600 mm	1000 mm	430 kg
Liebert NXC 120 kVA	120 kVA / 120 kW	380 / 400 / 415 VAC	380 / 400 / 415 VAC (3ph)	95.6% (100% Load)	1600 mm	600 mm	1000 mm	430 kg
Liebert NXC 160 kVA	160 kVA / 160 kW	380 / 400 / 415 VAC	380 / 400 / 415 VAC (3ph)	95.5% (100% Load)	2000 mm	600 mm	1000 mm	475 kg
Liebert NXC 200 kVA	200 kVA / 200 kW	380 / 400 / 415 VAC	380 / 400 / 415 VAC (3ph)	95.3% (100% Load)	2000 mm	600 mm	1000 mm	520 kg